

CLAIMS

1. A method for switching on a subscriber signal, the method comprising the steps of:
- 5 defining a transmission path from a calling terminal device of a switched-through telecommunications network to a called terminal device of a packet transmission network using a network gateway function;
- indicating, via a signaling message which is defined for the packet transmission network and which comes from the called terminal device end, that
- 10 the called terminal device is signaling the call to a subscriber;
- generating, when the signaling message which is defined for the packet transmission network occurs, a following signaling message which indicates that a subscriber signal has not yet been generated for the calling terminal device;
- processing the following signaling message, wherein the switching-on of the
- 15 subscriber signal for the calling terminal device is brought about; and
- generating a standard signaling message which is defined for the switched-through telecommunications network and which indicates that a subscriber signal has already been generated for the calling terminal device.
- 20 2. A method for switching on a subscriber signal as claimed in claim 1, wherein the following signaling message is a signaling message which is defined for the switched-through telecommunications network and with which it is indicated that sufficient dialing digits have been transmitted.
- 25 3. A method for switching on a subscriber signal as claimed in claim 1, wherein at least one of the standard signaling message and the following signaling message is a signaling message which has a structure which is defined in a standard which is one of an ISUP standard, a BICC standard, and a standard which is based on one of these standards.

30

4. A method for switching on a subscriber signal as claimed in claim 1, wherein the following signaling message is a signaling message which is defined for the signaling within a switching office of the switched-through network.
5. A method for switching on a subscriber signal as claimed in claim 1, wherein signaling messages with a same structure as the following signaling message are transmitted, within a switching office of the switched-through network, to at least one of connecting units for connecting subscribers, connecting units for connecting user data transmission paths to other switching offices of the switched-through network, and connecting units for providing the network gateway function.
6. A method for switching on a subscriber signal as claimed in claim 1, wherein the network gateway function is provided using at least two spatially separated units.
7. A method for switching on a subscriber signal as claimed in claim 6, the method further comprising the steps of:
transmitting, via a network gateway unit, the user data between the switched-through telecommunications network and the packet transmission network; and
controlling the network gateway unit by a spatially remote control unit, via a defined control protocol which is one of protocol H.248, protocol MGCP, and a protocol based on one of these protocols.
8. A method for switching on a subscriber signal as claimed in claim 6, the method further comprising the step of:
transmitting the standard signaling message via a switching office of the switched-through telecommunications network.
9. A method for switching on a subscriber signal as claimed in claim 8, the method further comprising the step of:

transmission path between a switching office which brings about the switching on of the subscriber signal and a unit on the network gateway function.

16. A method for switching on a subscriber signal as claimed in claim 1,
5 wherein the switching office which brings about the switching on is an originating switching office to which the calling terminal device is connected.

17. A method for switching on a subscriber signal as claimed in claim 1,
wherein the subscriber signal is fed into a unit for transferring user data between the
10 switched-through telecommunications network and the packet transmission network.

18. A method for switching on a subscriber signal as claimed in claim 1,
wherein the subscriber signal is one of a ringing tone and an announcement which
15 indicates that the called terminal device is signaling the call for a subscriber.

19. A method for switching on a subscriber signal as claimed in claim 1,
wherein the following signal message contains an indicator whose value depends
on whether the called terminal device is occupied, the indicator of an occupied state
20 and the indicator of the subscriber signal are checked by reference to the following signaling message, and the switching on of the subscriber signal is brought about only if the called terminal device is free and the subscriber signal has not yet been generated.

20. A method for switching on a subscriber signal as claimed in claim 1,
wherein a switching office is provided such that during operation of the switching
office the method is carried out.

21. A method for switching on a subscriber signal as claimed in claim 1,
30 wherein upon execution of an instruction sequence of a program, the method is carried out by a processor.